

液压破碎锤

Hydraulic Breaker

1. 高效能设计
2. 超高性价比
3. 超级打击力
4. 精巧的制造工艺和专业的热处理工艺

1. High efficiency design
2. Superior CPR (cost-performance ratio)
3. Super impact power
4. Exquisite manufacturing engineering and specific heat treatment



静音式
SILENCE

塔式
TOP

三角式
SIDE

HYDRAULIC BREAKER

性能参数
Specification And Parameters

型号 Model	GT08	GT10	GT20	GT30	GT40	GT50	GT60	GT70	GT75	
钎杆直径 (mm) Tool Dia	40	45	53	70	75	85	100	120	125	
钎杆重量 (kg) Tool Weight	4	6	9	19	24	32	57	89	98	
工作重量 (kg) Operating Weight	三角式 Silence	137	195	260	390	480	648	917	1358	1415
	塔式 Top	91	122	153	330	458	591	880	1420	1578
	静音式 Side	81	102	140	264	345	493	736	1374	1484
工作流量 (l/min) Operating Flux	15-30	20-40	25-50	40-70	50-90	60-100	80-110	90-120	90-120	
工作压力 (bar) Operating Pressure	90-120	90-120	90-120	110-140	120-150	130-160	150-170	150-170	150-170	
冲击频率 (bmp) Impact Rate	800-1400	700-1200	600-1200	500-900	400-800	400-800	350-700	350-650	350-650	
配套挖机 Applicable Excavator	斗容 (m ³) Capacity	≤0.07	0.03-0.1	0.06-0.2	0.15-0.3	0.20-0.35	0.25-0.5	0.4-0.6	0.5-0.7	0.5-0.75
	机重 (ton) Weight	0.8-2.5	1.2-3.0	2.5-4.5	4.0-7.0	6.0-9.0	7.0-14	11-16	12-18	14-20

型号 Model	GT80	GT90	GT100	GT130	GT150	GT160	GT190	GT200	
钎杆直径 (mm) Tool Dia	135	140	140	150	155	155	160	175	
钎杆重量 (kg) Tool Weight	131	142	140	164	183	197	200	263	
工作重量 (kg) Operating Weight	三角式 Silence	1712	1947	2018	2145	2676	2691	2791	3532
	塔式 Top	1890	2123	2121	2282	2935	3058	3007	3684
	静音式 Side	1633	1890	1887	2352	2841	2923	3075	3600
工作流量 (l/min) Operating Flux	100-150	120-180	150-190	150-190	180-240	190-250	190-250	210-290	
工作压力 (bar) Operating Pressure	160-180	160-180	160-180	160-180	160-180	160-180	160-180	160-180	
冲击频率 (bmp) Impact Rate	350-600	350-500	350-500	350-500	350-450	300-450	300-450	200-350	
配套挖机 Applicable Excavator	斗容 (m ³) Capacity	0.6-1.0	0.85-1.2	0.85-1.2	1.1-1.5	1.2-1.6	1.2-1.6	1.3-1.8	1.4-2.0
	机重 (ton) Weight	18-23	19-25	20-28	25-32	28-35	30-40	35-45	40-55

